




# HUMM-VAC™ VACUUM PUMPS



**Pump Specifications**

	<b>HVP6</b>	<b>HVP8</b>	<b>HVP12</b>	<b>UVP1.5</b>
Free Air Displacement	6.0 CFM, 170 liter/min.	8.0 CFM, 226 liter/min.	12.0 CFM 340 liter/min.	1.5 CFM, 40.5 liter/min.
Number of Stages	2-Stage Rotary Vane	2-Stage Rotary Vane	2-Stage Rotary Vane	2-Stage Rotary Vane
Factory Micron Rating	15 Microns	15 Microns	15 Microns	38 Microns
Intake Fittings	¼" and ⅜" Male Flare; ½" Acme	¼", ⅜" and ½" Male Flare	¼", ⅜" and ½" Male Flare	¼" Male Flare & ½" Acme
Thermal Overload Protection	1/2 HP	3/4 HP	3/4 HP	1/4 HP
Voltage	110/220V - 50/60Hz	110/220V - 50/60Hz	110/220V - 50/60Hz	†[see below]
Oil Capacity	1 Quart (946 ml)	31.3 Ounces (925 ml)	27.7 Ounces (820 ml)	4.7 Ounces (140 ml)
Power Cord	72" (1.83m)	72" (1.83m)	72" (1.83m)	66" (1.68m)
Dimensions	14.50" x 6.875" x 10.75"	15.0" x 6.875" x 10.75"	15.0" x 6.875" x 10.75"	10.23" x 3.50" x 6.40"
	36.83 cm x 17.46 cm x 27.30 cm	38.1 cm x 17.46 cm x 27.3 cm	38.1 cm x 17.46 cm x 27.3 cm	26 cm x 9 cm x 16.5 cm
Weight	26 Lbs. (11.80 kg)	34 Lbs. (15.42 kg)	35 Lbs. (15.88 kg)	9.9 Lbs. (4.5 Kg)
Shipping Weight	30 Lbs. (13.60 kg)	38 Lbs. (17.24 kg)	39 Lbs. (17.70 kg)	14 Lbs. (6.3 Kg)
Color	Yellow	Red	Black	Black

**USE ONLY PREMIUM UNIWELD VACUUM PUMP OIL**

- 42005** Quart (.946 liter) 12 per case
- 42006** Gallon (3.78 liters) 6 per case



† **UVP1.5-110** [110V-50/60 Hz]  
 † **UVP1.5-220** [220V-50/60 Hz]



**UNIWELD PRODUCTS, INC.**

2850 Ravenswood Road, Fort Lauderdale, FL 33312  
 Customer Service: 800.323.2111 • 954.584.2000 • Fax: 954.587.0109  
 www.uniweld.com • info@uniweld.com



**UVP1.5**

**UNIWELD®**  
**PRODUCTS, INC.**  
 FT. LAUDERDALE  
 FL 33312 U.S.A.  
 www.uniweld.com



RESIDENTIAL AND COMMERCIAL

# HUMM•VAC™ VACUUM PUMPS

- COOL NEW STYLING
- WIDE SUREFOOTED CHASSIS
- LIGHTWEIGHT



- SLANT BACK BALANCED HANDLE
- TOP MOUNT 1/4 TURN ON/OFF ISOLATION VALVE
- GAS BALLAST
- LOW PROFILE BEVELED OIL DRAIN
- LARGE OIL LEVEL SIGHT GLASS

The all-new Uniweld exclusive HUMM•VAC pumps: HVP 6CFM (yellow) and its two bigger brothers, HVP 8CFM (red) and HVP 12CFM (black) remove moisture and dehydrate a system quickly and efficiently. The rugged tough chassis, powerful, quiet running 110/220V, 50/60 Hz motors, lighter weight and ergonomically designed features make these pumps the #1 choice to go to work with you.

ALL NEW PATENTED DESIGN



- DEEP VACUUM PULL

U.S. PAT. #D0518068



HVP12

HVP8

HVP6